

Machine outlet IP67

INDUSTRIAL ETHERNET



VARIOSUB, HAN® 3A



Type

**Ind.Outlet Metal, Cat.6
RJ45-IP67-VARIOSUB
PHOENIX**

**Ind.Outlet Metal, Cat.5
RJ45-IP67 HAN 3A HARTING**

Configuration

Housing material:
Colour:
Board:
Push-on connector type:
Outlet direction:
Number of bushes:
Type of screen:
Strain relief:
Cable inlet:

Aluminium die-cast, shielded
Grey
1x2
RJ45(8/8)
Straight
2
Overall screen
via pre-installed cable clips
horizontal
vertical
67

Aluminium die-cast, shielded
Grey
1x2
RJ45(8/8)
Straight
2
Overall screen
via pre-installed cable clips
horizontal
vertical
67

Protection classification (IP):

Connecting system

Connection type:
Suitable for cable diameter:
Insulation diameter, min.:

LSA plus - insulation piercing connections
0,4 - 0,64mm (AWG 26 - 22)
0,7 - 1,7 mm (PE)

LSA plus - insulation piercing connections
0,4 - 0,64mm (AWG 26 - 22)
0,7 - 1,7 mm (PE)

Assignment type

EIA/TIA 568 A + EIA/TIA 568 B

EIA/TIA 568 A + EIA/TIA 568 B

Dimension

Installation dimensions:

175 x 110 x 45mm

175 x 110 x 45mm

Norms and standards

HELUKAT® CONNECTING SYSTEMS INDUSTRY® components up to 100 MHz category 5 in accordance with ISO/IEC 11801 2nd Edition, EN50173 2nd Edition. Moreover it satisfies the MICE specifications (class 3), EMC requirements in accordance with DIN EN 6100, and the requirements of the IP 67 housing protection class.

Application

Robust data connection socket (shielded) for the extreme implementation. Robust aluminum die-cast housing, meets all mechanical requirements like vibration, shock, and transverse forces. The socket is used either on the machine distributor (MD) or wall mounted directly on the machine (MC) as connection unit.

Part no.

801278

801306

Dimensions and specifications may be changed without prior notice.

Packing unit

5

5