

Outlet top hat rail

INDUSTRIAL ETHERNET



RJ45, horizontal/vertical



Type

Configuration

Housing material:
Colour:
Board:
Push-on connector type:
Outlet direction:
Number of bushes:
Type of screen:
Strain relief:
Cable inlet:

Plastic, shielded
Pure White similar to RAL 9010
1x2
RJ45(8/8)
45 degrees
2
Overall screen
via pre-installed cable clips
horizontal

Plastic, shielded
Pure White similar to RAL 9010
1x2
RJ45(8/8)
45 degrees
2
Overall screen
via pre-installed cable clips
vertical

Connecting system

Connection type:
Suitable for cable diameter:
Insulation diameter, min.:

LSA plus - insulation piercing connections
0,4 - 0,64mm (AWG 26 - 22)
0,7 - 1,7 mm (PE)

LSA plus - insulation piercing connections
0,4 - 0,64mm (AWG 26 - 22)
0,7 - 1,7 mm (PE)

Assignment type

EIA/TIA 568 A + EIA/TIA 568 B

EIA/TIA 568 A + EIA/TIA 568 B

Dimension

Dimensions of central plate:
Installation dimensions:

50 x 50mm
80 x 80 x 46mm

50 x 50mm
80 x 80 x 46mm

Norms and standards

HELUKAT® CONNECTING SYSTEMS® INDUSTRY system component up to 250 MHz in the permanent link of category 6 or Class E in accordance with ISO 11801, 2nd edition, EN 50173, 2nd edition, EIA/TIA 568 B, and EN 55022 (EMC)

Application

As connection unit for DIN rail installation e.g. in the switch cabinet, for applications involving digital and analog image, data and voice transmission.

Part no.

801308

801309

Dimensions and specifications may be changed without prior notice.

Packing unit

10

10