

Patch Cables PROFINet A



RJ45 angled left, INDUSTRIAL IP20



Type

Patch Cable RJ45 HARTING Industrial IP20 angled left, PROFINet A fixed installation

Cable

Designation:
Sheath material:
Frequency:

PROFINet type A (SK)
PVC
up to 100 MHz

Plug

Push-on connector type 1:
Push-on connector type 2:
System type:
Pin assignment:

RJ45-connector IP20
open
Harting RJ Robust IP20 angled left
1:1 acc. to TIA/EIA 568 B

Flame proof

acc. to IEC 60332-1-2

Oil-resistant

Acc. to EN60811-2-1

Norms and standards

Components of HELUKAT® CONNECTING SYSTEMS® to 100 MHz acc. Categorie 5, ISO 11801 1st Edition, EN 50173-3, EIA/TIA 568 B and IEC 60603-7. Support the PROFINet guideline V 1.8.

Preferred types

Part no.	Sheath colour	Length in metres	Unit
802410	green	0,5	10
802411	green	1,0	10
802412	green	2,0	10
802413	green	3,0	10
802414	green	5,0	10
802415	green	10,0	10

Dimensions and specifications may be changed without prior notice.

Characteristics

Jumper cable for the connection between IP20 protected ethernet applications according ISO/IEC 11801 with RJ45 plug, second side without plug. Usable for fixed installation cabling within cabinets or controllers.

Options

We also can deliver other cable length, cross-over cables or other types of plugs.