

B solderless terminals

non insulated



Solderless terminals type B


Non-insulated solderless terminals in eye type design.

Material

Copper
Surface: tinned

Technical data

Temperature range: up to +125°C



Dimensions

a Diameter of the boring
d Inner diameter of the cable insertion
b Flange width
l Length till middle of the boring

eye type

Part no.	Type	Cross-section mm ²	a mm	b mm	d mm	t mm	l mm	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
										up to 500	501 - 1000	1001 - 5000
91514	B 1-3	0,5-1,5	3,2	6,0	1,6	1,0	11,0	0,7	100	o. r.	o. r.	o. r.
91515	B 1-4	0,5-1,5	4,3	8,0	1,6	1,0	12,0	0,8	100	o. r.	o. r.	o. r.
91516	B 1-5	0,5-1,5	5,3	10,0	1,6	1,0	13,0	0,8	100	o. r.	o. r.	o. r.
91517	B 2,5-3	1,5-2,5	3,2	6,0	2,3	1,0	11,0	0,6	100	o. r.	o. r.	o. r.
91518	B 2,5-4	1,5-2,5	4,3	8,0	2,3	1,0	12,0	0,8	100	o. r.	o. r.	o. r.
91519	B 2,5-5	1,5-2,5	5,3	10,0	2,3	1,0	14,0	0,9	100	o. r.	o. r.	o. r.
91520	B 2,5-6	1,5-2,5	6,5	11,0	2,3	1,0	16,0	1,1	100	o. r.	o. r.	o. r.
91521	B 6-4	2,5-6,0	4,3	8,0	3,6	1,0	14,0	1,4	100	o. r.	o. r.	o. r.
91522	B 6-5	2,5-6,0	5,3	10,0	3,6	1,0	15,0	1,5	100	o. r.	o. r.	o. r.
91523	B 6-6	2,5-6,0	6,5	11,0	3,6	1,0	16,0	1,6	100	o. r.	o. r.	o. r.
91524	B 6-8	2,5-6,0	8,4	14,0	3,6	1,0	19,0	2,1	100	o. r.	o. r.	o. r.
91525	B 10-5	10	5,3	10,0	4,5	1,1	16,0	2,3	100	o. r.	o. r.	o. r.
91526	B 10-6	10	6,5	11,0	4,5	1,1	17,0	2,4	100	o. r.	o. r.	o. r.
91527	B 10-8	10	8,4	14,0	4,5	1,1	20,0	2,9	100	o. r.	o. r.	o. r.
91528	B 16-5	16	5,3	11,0	5,8	1,2	20,0	3,9	100	o. r.	o. r.	o. r.
91529	B 16-6	16	6,5	11,0	5,8	1,2	20,0	3,8	100	o. r.	o. r.	o. r.
91530	B 16-8	16	8,4	14,0	5,8	1,2	22,0	4,2	100	o. r.	o. r.	o. r.
91531	B 16-10	16	10,5	18,0	5,8	1,2	24,0	4,9	100	o. r.	o. r.	o. r.
91532	B 25-6	25	6,5	12,0	7,5	1,5	25,0	7,1	50	o. r.	o. r.	o. r.
91533	B 25-8	25	8,4	16,0	7,5	1,5	25,0	7,6	50	o. r.	o. r.	o. r.
91534	B 25-10	25	10,5	18,0	7,5	1,5	26,0	7,4	50	o. r.	o. r.	o. r.
91535	B 35-8	35	8,4	16,0	9,0	1,6	26,0	9,7	50	o. r.	o. r.	o. r.
91536	B 35-10	35	10,5	18,0	9,0	1,6	27,0	9,9	50	o. r.	o. r.	o. r.
91537	B 35-12	35	13,0	22,0	9,0	1,6	31,0	11,0	50	o. r.	o. r.	o. r.
91538	B 50-8	50	8,4	18,0	11,0	1,8	34,0	7,9	50	o. r.	o. r.	o. r.
91539	B 50-10	50	10,5	18,0	11,0	1,8	34,0	16,7	50	o. r.	o. r.	o. r.
91540	B 50-12	50	13,0	22,0	11,0	1,8	36,0	17,7	50	o. r.	o. r.	o. r.
91541	B 70-10	70	10,5	22,0	13,0	2,0	38,0	25,2	25	o. r.	o. r.	o. r.
91542	B 70-12	70	13,0	22,0	13,0	2,0	38,0	21,8	25	o. r.	o. r.	o. r.
91543	B 70-16	70	17,0	28,0	13,0	2,0	42,0	25,6	25	o. r.	o. r.	o. r.
91544	B 95-10	95	10,5	24,0	15,0	2,5	42,0	40,0	25	o. r.	o. r.	o. r.
91545	B 95-12	95	13,0	24,0	15,0	2,5	42,0	35,7	25	o. r.	o. r.	o. r.
91546	B 95-16	95	17,0	28,0	15,0	2,5	44,0	40,0	25	o. r.	o. r.	o. r.
97765	B 120-10	120	10,5	24,0	17,0	3,0	44,0	56,0	25	o. r.	o. r.	o. r.
97766	B 120-12	120	13,0	24,0	17,0	3,0	44,0	54,0	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request