

ADI-B core end sleeves



ADI-B

Tape products for processing with Stripax-Plus (strip products) or automatic crimpers (coil products).

Insulated core end sleeves prevent stripped wires from fanning.
The hopper-shaped plastic collar enables them to be pushed easily onto the wires.

Material

Sleeve: copper
Surface: tinned


Insulating shroud: polypropylene

Note

Delivery formats:
Strips: 1 item = 10 strips x 50 pcs.
Coils: Endless on cardboard coil

Technical data

Temperature range: up to +105°C
Temperature range temporary up to +120°C



Dimensions

L Total length
l Stick length

strip

Part no.	Size mm ²	Colour	Colour code	Total length mm	Stick length mm	Unit	Net EUR/100 items at a purchase of			
							up to 5000	5001 - 10000	10001 - 50000	
91912	0,5	white	DIN	14,0	8,0	500	o. r.	o. r.	o. r.	
91913	0,5	orange	Z+F	14,0	8,0	500	o. r.	o. r.	o. r.	
91914	0,75	grey	DIN	14,0	8,0	500	o. r.	o. r.	o. r.	
91915	0,75	white	Z+F	14,0	8,0	500	o. r.	o. r.	o. r.	
91916	0,75	light blue	Telemecanique	14,0	8,0	500	o. r.	o. r.	o. r.	
91917	1,0	red	DIN	14,0	8,0	500	o. r.	o. r.	o. r.	
91918	1,0	yellow	Z+F	14,0	8,0	500	o. r.	o. r.	o. r.	
91919	1,5	black	DIN	14,0	8,0	500	o. r.	o. r.	o. r.	
91920	1,5	red	Z+F	14,0	8,0	500	o. r.	o. r.	o. r.	
91921	2,5	blue	DIN	14,0	8,0	500	o. r.	o. r.	o. r.	
91922	2,5	grey	Telemecanique	14,0	8,0	500	o. r.	o. r.	o. r.	

coils

Part no.	Size mm ²	Colour	Colour code	Total length mm	Stick length mm	Unit	Net EUR/100 items at a purchase of			
							up to 5000	5001 - 10000	10001 - 50000	
93036	0,5	white	DIN	14,0	8,0	10000	o. r.	o. r.	o. r.	
93037	0,5	orange	Z+F	14,0	8,0	10000	o. r.	o. r.	o. r.	
93038	0,75	light blue	Telemecanique	14,0	8,0	10000	o. r.	o. r.	o. r.	
93039	0,75	white	Z+F	14,0	8,0	10000	o. r.	o. r.	o. r.	
93040	0,75	grey	DIN	14,0	8,0	10000	o. r.	o. r.	o. r.	
93041	1,0	red	DIN	14,0	8,0	7500	o. r.	o. r.	o. r.	
93042	1,0	yellow	Z+F	14,0	8,0	7500	o. r.	o. r.	o. r.	
93043	1,5	black	DIN	14,0	8,0	7500	o. r.	o. r.	o. r.	
93046	1,5	red	Z+F	14,0	8,0	7500	o. r.	o. r.	o. r.	
93047	2,5	grey	Telemecanique	14,0	8,0	5000	o. r.	o. r.	o. r.	
93048	2,5	blue	DIN	14,0	8,0	5000	o. r.	o. r.	o. r.	

Dimensions and specifications may be changed without prior notice.

o. r. = on request