



CNP

Fully plastic, UL/CSA approval.
Extremely abrasion-resistant plastic tube for heavy-duty applications.
A neoprene internal tube with nylon weave and abrasion-proof special PVC sheath.
Very good UV- and oil-resistance

Material

PVC
UV-resistant

Outer sheath material: PVC
With woven nylon insert

Technical data

Protection class: IP 67

Temperature range: -20°C up to +60°C
Temperature range temporary up to +80°C

Note

Suitable connection glands:
LT-CNP and LT-CNP-E

Part no. orange	Trade size inch	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
91259	3/8"	12,6	19,4	76	o. r.	o. r.	o. r.
91260	1/2"	16,1	23,4	60	o. r.	o. r.	o. r.
91261	3/4"	21,0	29,5	53	o. r.	o. r.	o. r.
91262	1"	26,5	36,3	30	o. r.	o. r.	o. r.
91263	1 1/4"	35,1	46,0	15	o. r.	o. r.	o. r.
91264	1 1/2"	40,7	52,4	15	o. r.	o. r.	o. r.
91265	2"	52,4	66,6	15	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request