



HFX

Halogen-free, low smoke generation, UV-resistant, oil-resistant, weather-resistant. Protection tube from reinforced, galvanised steel band with spiral wound, latched profile, a continuous cord seal and extruded plastic sheath.

This complex construction method keeps the plastic sheath and the internal tube flush together.

Material

Galvanised steel
UV-resistant

Outer sheath material: Polyurethane

- halogen-free

Properties

Low toxicity in case of fire.
Flexible at low temperatures, very good UV-resistance and oil resistance.
EN standard approved tube, for the railways, tunnels, ships, public buildings.

Note

Suitable connection glands:
T&B straight, T&B angled, Anamet straight, Anamet angled

Technical data

Protection class: IP 67

Temperature range: -45°C up to +105°C
Temperature range temporary up to +125°C

Part no. black	Trade size inch	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
94994	5/16"	10,1	14,4	30	o. r.	o. r.	o. r.
94995	3/8"	12,6	17,8	30	o. r.	o. r.	o. r.
94996	1/2"	16,0	21,1	30	o. r.	o. r.	o. r.
94997	3/4"	21,0	26,4	30	o. r.	o. r.	o. r.
94998	1"	26,5	33,1	30	o. r.	o. r.	o. r.
94999	1 1/4"	35,1	41,8	15	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request