



HTDL

UL/CSA approval, good EMC properties.

Protection tube from reinforced, galvanised steel band with spiral wound, latched profile, a continuous copper conductor and extruded plastic sheath.

This complex construction method keeps the plastic sheath and the internal tube flush together.

Material

Galvanised steel
UV-resistant

Outer sheath material: PVC

Note

Suitable connection glands:
LT straight, LT angled, T&B straight, T&B angled.
Up to 1 1/4" with copper conductor.

Technical data

Protection class: IP 67

Temperature range: -45°C up to +105°C
Temperature range temporary up to +120°C

Part no. black	Trade size inch	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
98149	3/8"	12,6	17,8	60	o. r.	o. r.	o. r.
98150	1/2"	16,1	21,1	60	o. r.	o. r.	o. r.
98151	3/4"	21,1	26,4	45	o. r.	o. r.	o. r.
98152	1"	26,8	33,1	30	o. r.	o. r.	o. r.
98153	1 1/4"	35,4	41,8	15	o. r.	o. r.	o. r.
98154	1 1/2"	40,3	47,8	15	o. r.	o. r.	o. r.
98155	2"	51,6	59,9	15	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request