

Anaconda Sealtite® OR for extensive chemical resistance



OR

Resistant to oil, grease, alkalis and acids.
Protection tubes from reinforced, galvanised steel band with spiral wound, latched profile, a continuous cord seal and extruded plastic sheath.

This complex construction method keeps the plastic sheath and the internal tube flush together.

Material

Galvanised steel
UV-resistant

Outer sheath material: Special PVC

Note

Suitable connection glands:
LT straight, LT angled, T&B straight, T&B angled.

Technical data

Protection class: IP 67

Temperature range: -15°C up to +100°C
Temperature range temporary up to +120°C

Part no. black	Trade size inch	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
91245	3/8"	12,6	17,8	75	o. r.	o. r.	o. r.
91246	1/2"	16,0	21,1	60	o. r.	o. r.	o. r.
91247	3/4"	21,0	26,4	50	o. r.	o. r.	o. r.
91248	1"	26,5	33,1	30	o. r.	o. r.	o. r.
91249	1 1/4"	35,1	41,8	30	o. r.	o. r.	o. r.
91250	1 1/2"	40,3	47,8	15	o. r.	o. r.	o. r.
91251	2"	51,6	59,9	15	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request