



ZHLS

Halogen-free, low smoke generation.
Protection tube from reinforced, galvanised steel band with spiral wound, latched profile, a continuous cord seal and extruded plastic sheath.

This complex construction method keeps the plastic sheath and the internal tube flush together.

Material

UV-resistant

Outer sheath material: Polyolefine

- halogen-free

Note

Suitable connection glands:
LT straight, LT angled, T&B straight, T&B angled

Technical data

Protection class: IP 67

Temperature range: -25°C up to +80°C

Temperature range temporary up to +100°C

Part no. black	Trade size inch	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
94988	5/16"	10,1	14,4	30	o. r.	o. r.	o. r.
94989	3/8"	12,6	17,8	30	o. r.	o. r.	o. r.
94990	1/2"	16,0	21,1	30	o. r.	o. r.	o. r.
94991	3/4"	21,0	26,4	30	o. r.	o. r.	o. r.
94992	1"	26,5	33,1	30	o. r.	o. r.	o. r.
94993	1 1/4"	35,1	41,8	15	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request