

HELUcond CO-PA corrugated tubes, polyamide

dividable



HELUcond CO-PA

The dividable and reclosable cable protection tube for subsequent mechanical protection of the cables.

- Trouble-free retrofitting
- High mechanical strength
- Simple installation of pre-fabricated lines
- Repair of existing systems

Application

- Plant and machine construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Polyamide 6
UV-resistant

Flammability acc. to UL 94: V2

- halogen-free

Properties

Resistant to a multitude of:

- fuels
- mineral oils
- greases
- weak bases
- weak acids

Note

Suitable connection glands:
COV

Technical data

Temperature range: -40°C up to +120°C
Temperature range temporary up to +150°C

Part no. black	trade size mm	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
90061	10,0	8,8	13,5	50	o. r.	o. r.	o. r.
90062	14,0	13,2	18,7	50	o. r.	o. r.	o. r.
90063	20,0	20,2	25,7	50	o. r.	o. r.	o. r.
90064	23,0	23,9	31,3	50	o. r.	o. r.	o. r.
90065	37,0	32,5	43,2	25	o. r.	o. r.	o. r.
90066	45,0	43,1	54,2	25	o. r.	o. r.	o. r.
920179	70,0	67,0	79,8	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request