

# HELUcond CO-PP corrugated tubes, polypropylene

dividable



## HELUcond CO-PP

The dividable and reclosable cable protection tube for subsequent mechanical protection of the cables.

- Trouble-free retrofitting
- High mechanical strength
- Simple installation of pre-fabricated lines
- Repair of existing systems

## Application

- Plant and machine construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

## Material

Polypropylene

Flammability acc. to UL 94: HB

- halogen-free

## Properties

resistant to a multitude of

- fuels
- mineral oils
- greases
- weak bases
- weak acids

## Note

Suitable connection glands:  
COV

## Technical data

Temperature range: -40°C up to +135°C

Temperature range temporary up to +150°C

Part no. black	trade size mm	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
97496	10,0	8,4	13,4	50	o. r.	o. r.	o. r.
97134	14,0	12,5	18,5	50	o. r.	o. r.	o. r.
97135	20,0	19,2	25,3	50	o. r.	o. r.	o. r.
97205	23,0	23,4	30,8	50	o. r.	o. r.	o. r.
96732	37,0	31,0	41,4	25	o. r.	o. r.	o. r.
90054	45,0	42,7	54,0	25	o. r.	o. r.	o. r.
920180	70,0	67,5	79,8	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request