



HSK-MS-E-D

The EMC cable gland to meet stringent requirements in technology. Time-saving and simple handling through metallised terminal insert, which is automatically contacted when the gland is closed.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Brass, nickel plated
Clamp: PA, metal-plated
Moulded seal: NBR
O-ring: NBR

Technical data

Protection class: IP 68 - 10 bar / IP 69K

Temperature range: -40°C up to +100°C



Dimensions

G Thread size
GL Thread length
SW Spanner size

metric thread

Part no.	Size Metr.	Cable Ø from / to mm	Thread length mm	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
98055	M12 x 1,5	3,0 - 6,5	6,5	14	50	o. r.	o. r.	o. r.
98056	M16 x 1,5	5,0 - 10,0	6,0	20	50	o. r.	o. r.	o. r.
98057	M20 x 1,5	10,0 - 14,0	6,0	24	50	o. r.	o. r.	o. r.
98058	M25 x 1,5	13,0 - 18,0	7,0	30	25	o. r.	o. r.	o. r.
98059	M32 x 1,5	18,0 - 25,0	8,0	40	25	o. r.	o. r.	o. r.
98060	M40 x 1,5	24,0 - 32,0	8,0	50	10	o. r.	o. r.	o. r.
90160	M50 x 1,5	32,0 - 38,0	9,0	57	5	o. r.	o. r.	o. r.
90161	M63 x 1,5	37,0 - 44,0	10,0	68	5	o. r.	o. r.	o. r.

PG thread

Part no.	Size PG	Cable Ø from / to mm	Thread length mm	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
97655	7	3,0 - 6,5	5,0	14	50	o. r.	o. r.	o. r.
97656	9	4,0 - 8,0	6,0	17	50	o. r.	o. r.	o. r.
97657	11	5,0 - 10,0	6,0	20	50	o. r.	o. r.	o. r.
97658	13,5	6,0 - 12,0	6,5	22	50	o. r.	o. r.	o. r.
97659	16	10,0 - 14,0	6,5	24	50	o. r.	o. r.	o. r.
97660	21	13,0 - 18,0	7,0	30	25	o. r.	o. r.	o. r.
97752	29	18,0 - 25,0	8,0	40	25	o. r.	o. r.	o. r.
97788	36	24,0 - 32,0	8,0	50	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request