

# IC insulating tube

PVC



## IC

PVC insulating tube for insulating and bundling wires and lines.

## Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Installation technology
- Control cabinet construction

## Material

PVC

Flammability acc. to UL 94: V2

- silicone-free

## Note

### Colour code:

Replace the "x" in the table with the following figures to obtain the product number of your required colour.

0=white, 1=blue, 2=yellow, 3=red,

4=transparent

5=green, 6=orange, 7=violet, 8=grey,

9=brown

## Technical data

DIN 40621

Temperature range: -20°C up to +90°C

## green/yellow

| Part no. | Inner Ø<br>mm | Wall<br>thickness<br>mm | Per<br>metres | Net EUR/100 metres at a purchase of |           |            |
|----------|---------------|-------------------------|---------------|-------------------------------------|-----------|------------|
|          |               |                         |               | up to 100                           | 101 - 500 | 501 - 1000 |
| 92280    | 1,0           | 0,4                     | 250,0         | o. r.                               | o. r.     | o. r.      |
| 92281    | 1,5           | 0,4                     | 250,0         | o. r.                               | o. r.     | o. r.      |
| 92282    | 2,0           | 0,4                     | 50,0          | o. r.                               | o. r.     | o. r.      |
| 92286    | 4,0           | 0,5                     | 50,0          | o. r.                               | o. r.     | o. r.      |
| 92289    | 6,0           | 0,55                    | 25,0          | o. r.                               | o. r.     | o. r.      |
| 92291    | 8,0           | 0,62                    | 25,0          | o. r.                               | o. r.     | o. r.      |
| 92292    | 10,0          | 0,75                    | 25,0          | o. r.                               | o. r.     | o. r.      |
| 92293    | 14,0          | 0,8                     | 25,0          | o. r.                               | o. r.     | o. r.      |
| 92294    | 16,0          | 0,8                     | 25,0          | o. r.                               | o. r.     | o. r.      |

## coloured

| Part no. | Inner Ø<br>mm | Wall<br>thickness<br>mm | Per<br>metres | Net EUR/100 metres at a purchase of |           |            |
|----------|---------------|-------------------------|---------------|-------------------------------------|-----------|------------|
|          |               |                         |               | up to 100                           | 101 - 500 | 501 - 1000 |
| 9210x    | 1,0           | 0,4                     | 50,0          | o. r.                               | o. r.     | o. r.      |
| 9211x    | 1,5           | 0,4                     | 50,0          | o. r.                               | o. r.     | o. r.      |
| 9212x    | 2,0           | 0,4                     | 50,0          | o. r.                               | o. r.     | o. r.      |
| 9213x    | 2,5           | 0,4                     | 50,0          | o. r.                               | o. r.     | o. r.      |
| 9214x    | 3,0           | 0,4                     | 50,0          | o. r.                               | o. r.     | o. r.      |
| 9215x    | 3,5           | 0,4                     | 50,0          | o. r.                               | o. r.     | o. r.      |
| 9216x    | 4,0           | 0,5                     | 50,0          | o. r.                               | o. r.     | o. r.      |
| 9217x    | 4,5           | 0,5                     | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9218x    | 5,0           | 0,52                    | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9219x    | 6,0           | 0,55                    | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9220x    | 7,0           | 0,6                     | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9221x    | 8,0           | 0,62                    | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9222x    | 10,0          | 0,7                     | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9223x    | 14,0          | 0,8                     | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9224x    | 16,0          | 0,8                     | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9225x    | 20,0          | 0,8                     | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9226x    | 26,0          | 1,0                     | 25,0          | o. r.                               | o. r.     | o. r.      |
| 9227x    | 36,0          | 1,0                     | 25,0          | o. r.                               | o. r.     | o. r.      |

Dimensions and specifications may be changed without prior notice.

o. r. = on request