

JUMBO-FP flange connection



JUMBO-FP

One-piece straight flange connection.
Suitable for parallel-coiled JUMBO protection tubes.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Polyamide PA 6

Flammability acc. to UL 94: VO

- halogen-free
- cadmium-free

Properties

resistant to a multitude of

- fuels
- mineral oils
- greases
- weak bases
- weak acids

Note

Additional seal increases protection
classification to IP 65

JUMBO sealing set:

Set contains 1 x O-ring and 1x cellular rubber
seal

Technical data

Protection class: IP 54

Temperature range: -40°C up to +115°C

flange connection

Part no. grey	Part no. black	Suitable for ND	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
90402	920368	70,0	1	o. r.	o. r.	o. r.
90403	920369	95,0	1	o. r.	o. r.	o. r.

seal inserts

Part no.	Colour	Suitable for ND	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
90406	black	70,0	1	o. r.	o. r.	o. r.
90407	black	95,0	1	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request