

KH-3, KH-4 sleeves for compacted conductors

not insulated



Sleeves KH-3, KH-4

Sleeves for compressed strands.

KH-3: 120°-sleeves for 3-core-cables.

KH-4: 90°-sleeves for 4-core-cables.

Sleeves will be slipped over the strand and circularly pressed, before crimping with cable lugs type K1 or K2.

Material

Sleeve: Copper

Surface: tinned

Technical data

Temperature range: up to +120°C



Dimensions

l Length

KH-3 for 3-core cable

Part no.	Type	Cross-section mm ²	d mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
								up to 500	501 - 1000	1001 - 5000
904664	KH-3 35	35,0	-	14,0	-	0,8	100	o. r.	o. r.	o. r.
904665	KH-3 50	50,0	-	17,0	-	1,7	50	o. r.	o. r.	o. r.
904666	KH-3 70	70,0	-	18,0	-	2,9	50	o. r.	o. r.	o. r.
904667	KH-3 95	95,0	-	22,0	-	4,5	50	o. r.	o. r.	o. r.
904668	KH-3 120	120,0	-	23,0	-	4,9	50	o. r.	o. r.	o. r.
904669	KH-3 150	150,0	-	25,0	-	5,8	25	o. r.	o. r.	o. r.
904670	KH-3 185	185,0	-	25,0	-	8,0	25	o. r.	o. r.	o. r.
904671	KH-3 240	240,0	-	30,0	-	10,4	25	o. r.	o. r.	o. r.

KH-4 for 4-core cable

Part no.	Type	Cross-section mm ²	d mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
								up to 500	501 - 1000	1001 - 5000
904672	KH-4 35	35,0	-	14,0	-	1,3	100	o. r.	o. r.	o. r.
904673	KH-4 50	50,0	-	17,0	-	1,7	50	o. r.	o. r.	o. r.
904674	KH-4 70	70,0	-	18,0	-	2,8	50	o. r.	o. r.	o. r.
904675	KH-4 95	95,0	-	22,0	-	4,0	50	o. r.	o. r.	o. r.
904676	KH-4 120	120,0	-	23,0	-	5,1	50	o. r.	o. r.	o. r.
904677	KH-4 150	150,0	-	25,0	-	5,7	25	o. r.	o. r.	o. r.
904678	KH-4 185	185,0	-	25,0	-	7,8	25	o. r.	o. r.	o. r.
904679	KH-4 240	240,0	-	30,0	-	8,5	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request