

KH-R sleeves for compacted conductors

not insulated



Sleeve KH-R

Sleeves for compressed strands. Sleeves will be slipped over the strand before crimping with cable lugs type K1 or K2.

Material


Sleeve: Copper
Surface: tinned

Note

For circular conductors

Technical data

Temperature range: up to +120°C



Dimensions

d Inner diameter of the cable insertion
l Length

KH-R for circular conductors

Part no.	Type	Cross-section mm ²	d mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
								up to 500	501 - 1000	1001 - 5000
904652	KH-R 16	16,0	5,0	11,0	-	0,2	100	o. r.	o. r.	o. r.
904653	KH-R 25	25,0	6,4	14,0	-	0,4	100	o. r.	o. r.	o. r.
904654	KH-R 35	35,0	7,7	15,0	-	0,8	100	o. r.	o. r.	o. r.
904655	KH-R 50	50,0	9,0	18,0	-	1,2	50	o. r.	o. r.	o. r.
904656	KH-R 70	70,0	10,6	19,0	-	1,7	50	o. r.	o. r.	o. r.
904657	KH-R 95	95,0	12,4	21,0	-	2,2	50	o. r.	o. r.	o. r.
904658	KH-R 120	120,0	13,9	22,0	-	2,6	50	o. r.	o. r.	o. r.
904659	KH-R 150	150,0	15,4	26,0	-	3,4	25	o. r.	o. r.	o. r.
904660	KH-R 185	185,0	17,6	26,0	-	4,0	25	o. r.	o. r.	o. r.
904661	KH-R 240	240,0	19,9	30,0	-	5,1	25	o. r.	o. r.	o. r.
904662	KH-R 300	300,0	22,4	38,0	-	7,2	10	o. r.	o. r.	o. r.
904663	KH-R 400	400,0	25,4	38,0	-	11,1	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request