

LT-CNP conduit gland

for Anaconda Sealbite® CNP



RoHS

Conduit gland LT-CNP straight

LIQUIDTIGHT gland made of galvanised steel for plastic-coated metallic protection tubes CNP.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Galvanised steel

Note

UL/CSA approval
The ferrule and insert are from PA 6

Technical data

Protection class: IP 67

Temperature range: -45°C up to +105°C

NPT thread

Part no.	Type	Size	Suitable for tube ND	Suitable for tube outer Ø mm	Thread length mm	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
								up to 100	101 - 500	501 - 1000
904907	-	1/2"	3/8	19,4	15,0	27,0	25	o. r.	o. r.	o. r.
904908	-	1/2"	1/2	23,4	15,0	32,0	25	o. r.	o. r.	o. r.
904909	-	3/4"	3/4	29,5	15,0	39,0	25	o. r.	o. r.	o. r.
904910	-	1"	1	36,3	18,0	45,0	5	o. r.	o. r.	o. r.
904911	-	1 1/4"	1 1/4	46,0	19,0	59,0	5	o. r.	o. r.	o. r.
904912	-	1 1/2"	1 1/2	52,4	19,0	67,0	2	o. r.	o. r.	o. r.
904913	-	2"	2	66,6	19,0	82,0	1	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request