

LT-E-UI conduit gland - 90°

stainless steel



LT-E-UI 90°

LIQUIDTIGHT conduit gland for stainless steel protection tubes UI.
The conical earthing sleeve offers maximum surface contact for optimum sealing and earthing.

Material

stainless steel
Grounding sleeve: Brass, nickel plated
Seal: Brass, nickel plated
Moulded seal: NBR

Technical data

Protection class: IP 40

Temperature range: -55°C up to +260°C

Application

- Robot construction
- Steel and aluminium foundry industry
- Machine and apparatus building
- Off-shore industry
- Security
- Metal, glass and ceramics industry

metric thread

Part no.	Size	Tube outer Ø mm	Thread length mm	Min. inner Ø mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
905832	M16 x 1,5	12,5	12,0	6,8	50	o. r.	o. r.	o. r.
905833	M16 x 1,5	16,0	12,0	9,8	50	o. r.	o. r.	o. r.
905834	M20 x 1,5	12,5	13,0	6,8	50	o. r.	o. r.	o. r.
905835	M20 x 1,5	16,0	13,0	9,8	50	o. r.	o. r.	o. r.
905836	M20 x 1,5	21,0	13,0	13,9	50	o. r.	o. r.	o. r.
905837	M25 x 1,5	26,0	15,0	18,5	25	o. r.	o. r.	o. r.

PG thread

Part no.	Size	Tube outer Ø mm	Thread length mm	Min. inner Ø mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
905838	11	12,5	12,0	6,8	50	o. r.	o. r.	o. r.
905839	11	16,0	12,0	9,8	50	o. r.	o. r.	o. r.
905840	16	21,0	13,0	13,9	50	o. r.	o. r.	o. r.
905841	21	26,0	15,0	18,5	25	o. r.	o. r.	o. r.
905842	29	30,0	15,0	22,8	10	o. r.	o. r.	o. r.

NPT thread

Part no.	Size	Tube outer Ø mm	Thread length mm	Min. inner Ø mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
905843	1/2"	12,5	12,0	6,8	50	o. r.	o. r.	o. r.
905844	1/2"	16,0	12,0	9,8	50	o. r.	o. r.	o. r.
905845	1/2"	21,0	13,0	13,9	50	o. r.	o. r.	o. r.
905846	3/4"	26,0	15,0	18,5	25	o. r.	o. r.	o. r.
905847	1"	30,0	15,0	22,8	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request