



Conduit gland LT 90°

LIQUIDTIGHT gland for plastic-coated metallic protection tubes and high temperature protection tubes HTP. (An additional clamping ring ist required). UL/CSA approval.

The conical earthing sleeve offers maximum surface contact for optimum sealing and earthing.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Brass, nickel plated
Grounding sleeve: Steel
Seal: Polyamide

Properties

- halogen-free

Note

Suitable for metallic protection tubes:
EF, HTDL, OR, HC, HCX, ZHLS, HFX, EMP

Technical data

Protection class: IP 67

Temperature range: -45°C up to +105°C

metric thread

Part no.	Size	Suitable for tube ND	Suitable for tube outer Ø mm	Spanner size mm	Thread length mm	Unit	Net EUR/100 items at a purchase of		
							up to 100	101 - 500	501 - 1000
94170	M16 x 1,5	3/8"	17,8	26,0	13,0	50	o. r.	o. r.	o. r.
94171	M20 x 1,5	1/2"	21,1	29,0	14,0	50	o. r.	o. r.	o. r.
94172	M25 x 1,5	3/4"	26,4	35,0	14,0	25	o. r.	o. r.	o. r.
94173	M32 x 1,5	1"	33,1	45,0	16,0	10	o. r.	o. r.	o. r.
920523	M40 x 1,5	1 1/4"	41,8	54,0	18,0	5	o. r.	o. r.	o. r.
920524	M50 x 1,5	1 1/2"	47,8	63,0	23,0	5	o. r.	o. r.	o. r.
920525	M63 x 1,5	2"	59,9	77,0	26,0	4	o. r.	o. r.	o. r.

PG thread

Part no.	Size	Suitable for tube ND	Suitable for tube outer Ø mm	Spanner size mm	Thread length mm	Unit	Net EUR/100 items at a purchase of		
							up to 100	101 - 500	501 - 1000
91022	11	3/8"	17,8	26,0	13,0	50	o. r.	o. r.	o. r.
91023	13,5	3/8"	17,8	26,0	13,0	50	o. r.	o. r.	o. r.
91024	16	1/2"	21,1	29,0	14,0	50	o. r.	o. r.	o. r.
91025	21	3/4"	26,4	35,0	14,0	25	o. r.	o. r.	o. r.
91026	29	1"	33,1	45,0	16,0	10	o. r.	o. r.	o. r.
91027	36	1 1/4"	41,8	54,0	18,0	5	o. r.	o. r.	o. r.
91028	42	1 1/2"	47,8	63,0	23,0	5	o. r.	o. r.	o. r.
91029	48	2"	59,9	77,0	26,0	4	o. r.	o. r.	o. r.

Continuation ►

o. r. = on request

LT conduit gland - 90°



NPT thread

Part no.	Size	Suitable for tube ND	Suitable for tube outer Ø mm	Spanner size mm	Thread length mm	Unit	Net EUR/100 Items at a purchase of		
							up to 100	101 - 500	501 - 1000
905763	1/2"	3/8"	17,8	26,0	12,0	50	o. r.	o. r.	o. r.
905764	1/2"	1/2"	21,1	29,0	13,0	50	o. r.	o. r.	o. r.
905765	3/4"	3/4"	26,4	35,0	15,0	25	o. r.	o. r.	o. r.
905766	1"	1"	33,1	45,0	15,0	10	o. r.	o. r.	o. r.
905767	1 1/4"	1 1/4"	49,0	54,0	16,0	5	o. r.	o. r.	o. r.
905768	1 1/2"	1 1/2"	36,8	63,0	18,0	5	o. r.	o. r.	o. r.
905769	2"	2"	66,0	77,0	20,0	4	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request