

N nickel tubular cable lug - straight

not insulated



Tubular cable lug K2

Non-insulated tubular cable lugs in eye type design. High definition version for reliable crimping.

Material

nickel

Properties

- Without inspection hole

Note

- a diameter hole
- d clearance
- b width
- t wall thickness
- l length to center of hole

Technical data

Temperature range: up to +500°C

eye type

Part no.	Type	Cross-section mm ²	a mm	d mm	b mm	t mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
											up to 100	101 - 500	501 - 1000
98267	N 1-4	0,5 - 1	4,3	1,6	6,5	0,8	13,0	-	0,8	100	o. r.	o. r.	o. r.
98268	N 1-5	0,5 - 1	5,3	1,6	7,5	0,8	14,0	-	0,8	100	o. r.	o. r.	o. r.
97805	N 2,5-4	1,5 - 2,5	4,3	2,3	7,0	0,8	13,0	-	1,1	100	o. r.	o. r.	o. r.
97806	N 2,5-5	1,5 - 2,5	5,3	2,3	7,5	0,8	14,0	-	1,1	100	o. r.	o. r.	o. r.
97807	N 2,5-6	1,5 - 2,5	6,5	2,3	9,5	0,8	16,0	-	1,3	100	o. r.	o. r.	o. r.
98269	N 6-4	4 - 6	4,3	3,6	9,5	1,0	18,0	-	2,8	100	o. r.	o. r.	o. r.
97808	N 6-5	4 - 6	5,3	3,6	9,5	1,0	19,0	-	2,8	100	o. r.	o. r.	o. r.
97809	N 6-6	4 - 6	6,5	3,6	9,5	1,0	19,0	-	2,6	100	o. r.	o. r.	o. r.
98270	N 10-5	10,0	5,5	4,5	12,0	1,0	21,0	-	3,4	100	o. r.	o. r.	o. r.
98271	N 10-6	10,0	6,5	4,5	12,0	1,0	22,0	-	3,6	100	o. r.	o. r.	o. r.
98272	N 16-5	16,0	5,5	5,5	12,0	1,0	26,0	-	4,7	100	o. r.	o. r.	o. r.
98273	N 16-6	16,0	6,5	5,5	12,0	1,0	27,0	-	4,8	100	o. r.	o. r.	o. r.
98274	N 16-8	16,0	8,5	5,5	13,5	1,0	29,0	-	5,6	100	o. r.	o. r.	o. r.
98275	N 25-6	25,0	6,5	7,0	14,0	1,5	30,0	-	12,0	50	o. r.	o. r.	o. r.
98276	N 25-8	25,0	8,5	7,0	16,0	1,5	32,0	-	13,2	50	o. r.	o. r.	o. r.
98277	N 35-6	35,0	6,5	8,5	17,0	1,75	32,0	-	18,5	50	o. r.	o. r.	o. r.
98278	N 35-8	35,0	8,5	8,5	17,0	1,75	34,0	-	20,0	50	o. r.	o. r.	o. r.
98279	N 50-8	50,0	8,5	10,0	20,0	2,0	37,0	-	29,0	50	o. r.	o. r.	o. r.
98280	N 50-10	50,0	10,5	10,0	20,0	2,0	39,0	-	31,0	50	o. r.	o. r.	o. r.
98281	N 70-10	70,0	10,5	12,0	23,0	2,25	44,0	-	46,0	25	o. r.	o. r.	o. r.
98282	N 70-12	70,0	13,0	12,0	23,0	2,25	46,0	-	46,6	25	o. r.	o. r.	o. r.
98283	N 95-10	95,0	10,5	13,5	26,0	2,25	48,0	-	55,5	25	o. r.	o. r.	o. r.
98284	N 95-12	95,0	13,0	13,5	26,0	2,25	49,0	-	56,0	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request