

O-ring FKM



O-ring FKM

O-rings for sealing against water, dust, and oil. Made by FKM for large temperature range.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction


Material

FKM

- halogen-free
- phosphor-free
- silicone-free
- cadmium-free

Technical data

Temperature range: -40°C up to +200°C



Dimensions

D Outer diameter
d Inner diameter
s Thickness

for metric thread

Part no.	Size metr.	Inner Ø mm	Outer Ø mm	Thickness mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
98594	M12 x 1,5	10,0	13,0	1,5	100	o. r.	o. r.	o. r.
98595	M16 x 1,5	12,0	15,0	1,5	100	o. r.	o. r.	o. r.
98596	M20 x 1,5	17,0	20,6	1,8	100	o. r.	o. r.	o. r.
904282	M25 x 1,5	22,0	26,0	2,0	100	o. r.	o. r.	o. r.
904283	M32 x 1,5	29,0	33,0	2,0	100	o. r.	o. r.	o. r.
904284	M40 x 1,5	35,0	39,0	2,0	50	o. r.	o. r.	o. r.
904285	M50 x 1,5	43,0	47,0	2,0	50	o. r.	o. r.	o. r.
904286	M63 x 1,5	55,0	59,0	2,0	50	o. r.	o. r.	o. r.

for PG thread

Part no.	Size PG	Inner Ø mm	Outer Ø mm	Thickness mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
97753	7	10,0	13,0	1,5	100	o. r.	o. r.	o. r.
904287	9	12,0	15,0	1,5	100	o. r.	o. r.	o. r.
904288	11	16,0	19,6	1,8	100	o. r.	o. r.	o. r.
904289	13,5	17,0	20,6	1,8	100	o. r.	o. r.	o. r.
96662	16	18,0	21,0	1,5	100	o. r.	o. r.	o. r.
904290	21	26,0	30,0	2,0	100	o. r.	o. r.	o. r.
904291	29	33,0	37,0	2,0	50	o. r.	o. r.	o. r.
904292	36	43,0	47,0	2,0	50	o. r.	o. r.	o. r.
904293	42	50,0	54,0	2,0	25	o. r.	o. r.	o. r.
904294	48	55,0	59,0	2,0	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request