



OF

Open folding profile for simple cable insertion.
The profile can be re-opened at any time.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material


Polyamide
O-ring: NBR

- halogen-free
- phosphor-free
- silicone-free
- cadmium-free

Technical data

Protection class: IP 68

Temperature range: -20°C up to +80°C



Dimensions

G Thread size outside
GL Thread length
IG Thread size inside

from metric to metric

Part no. light grey RAL 7035	Part no. black RAL 9005	Size Metr.	Thread length mm	Unit	Net EUR/100 items at a purchase of		
					up to 100	101 - 500	501 - 1000
90271	91835	M16 x 1,5	8,0	25	o. r.	o. r.	o. r.
90272	91836	M20 x 1,5	9,0	25	o. r.	o. r.	o. r.
90273	91837	M25 x 1,5	11,0	10	o. r.	o. r.	o. r.

from PG to PG

Part no. light grey RAL 7035	Part no. black RAL 9005	Size PG	Thread length mm	Unit	Net EUR/100 items at a purchase of		
					up to 100	101 - 500	501 - 1000
90383	97110	9	8,0	25	o. r.	o. r.	o. r.
90384	97502	11	8,0	25	o. r.	o. r.	o. r.
90385	97073	13,5	9,0	25	o. r.	o. r.	o. r.
90386	94781	16	10,0	25	o. r.	o. r.	o. r.
90387	94782	21	11,0	25	o. r.	o. r.	o. r.
90388	96102	29	11,0	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request