

# PV-A aluminium compression joint

not insulated



## Compression joint PV-A

Clamping connection sleeves for unstrained clamping of conductors built to DIN 46267.

RM/SM and SE conductor

## Material

Aluminium  
Surface: bare

## Note

Code type indicates the required hexagonal clamping insert.  
Part No. 93444 and Part No. 93445 are not standardised.

## Technical data

Temperature range: up to +120°C



## Dimensions

d Inner diameter of the cable inclusion  
l Length

## bare

Part no.	Type	Cross-section RM/SM mm <sup>2</sup>	Cross-section SE mm <sup>2</sup>	d mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
									up to 100	101 - 500	501 - 1000
93444	PV-A 10	10,0	-	5,0	55,0	10,0	9,5	10	o. r.	o. r.	o. r.
93445	PV-A 16	16,0	25,0	5,8	55,0	12,0	14,0	10	o. r.	o. r.	o. r.
93446	PV-A 25	25,0	35,0	6,8	70,0	12,0	16,0	10	o. r.	o. r.	o. r.
93290	PV-A 35	35,0	50,0	8,0	85,0	14,0	26,0	10	o. r.	o. r.	o. r.
93291	PV-A 50	50,0	70,0	9,8	85,0	16,0	32,0	10	o. r.	o. r.	o. r.
93292	PV-A 70	70,0	95,0	11,2	105,0	18,0	53,0	10	o. r.	o. r.	o. r.
93293	PV-A 95	95,0	120,0	13,2	105,0	22,0	76,0	10	o. r.	o. r.	o. r.
93294	PV-A 120	120,0	150,0	14,7	105,0	22,0	78,0	10	o. r.	o. r.	o. r.
93295	PV-A 150	150,0	185,0	16,3	125,0	25,0	107,0	10	o. r.	o. r.	o. r.
93296	PV-A 185	185,0	240,0	18,3	125,0	28,0	143,0	5	o. r.	o. r.	o. r.
93297	PV-A 240	240,0	300,0	21,0	145,0	32,0	203,0	5	o. r.	o. r.	o. r.
93298	PV-A 300	300,0	-	23,3	145,0	34,0	222,0	1	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request