

PV-AMÖ aluminium compression joint

not insulated



Compression joint PV-AMÖ

Clamping connection sleeves for unstrained clamping of Al medium-range voltage cables 10-30 kV.

On the PV-AMÖ, the centre web achieves a total oil stop.

Material

Sleeve: Aluminium
Surface: bare

Note

Code type indicates the required hexagonal clamping insert.

Technical data

Temperature range: up to +120°C



bare - with oil stop

Part no.	Type	Cross-section RM/SM mm ²	Cross-section SE mm ²	d mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
									up to 100	101 - 500	501 - 1000
99470	PV-AMÖ 35	35,0	50,0	8,0	95,0	14,0	31,0	5	o. r.	o. r.	o. r.
99471	PV-AMÖ 50	50,0	70,0	9,8	95,0	16,0	56,0	5	o. r.	o. r.	o. r.
99472	PV-AMÖ 70	70,0	95,0	11,2	100,0	18,0	61,0	5	o. r.	o. r.	o. r.
99473	PV-AMÖ 95	95,0	120,0	13,2	105,0	22,0	92,0	5	o. r.	o. r.	o. r.
99474	PV-AMÖ 120	120,0	150,0	14,7	110,0	22,0	103,0	5	o. r.	o. r.	o. r.
99475	PV-AMÖ 150	150,0	185,0	16,3	110,0	25,0	120,0	5	o. r.	o. r.	o. r.
99476	PV-AMÖ 185	185,0	240,0	18,3	130,0	28,0	156,0	5	o. r.	o. r.	o. r.
99477	PV-AMÖ 240	240,0	300,0	21,0	130,0	32,0	191,0	5	o. r.	o. r.	o. r.
99478	PV-AMÖ 300	300,0	-	23,3	135,0	34,0	307,0	1	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request