



T&B straight

Hose gland for Anaconda protection tubes.
The specific construction prevents the tubes becoming deformed during assembly.

Material

Galvanised steel chromate finish
Grounding sleeve: Steel
Seal: Polyamide

Technical data

Protection class: IP 67

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

metric thread

Part no.	Size	Suitable for tube ND	Suitable for tube outer Ø mm	Spanner size mm	Thread length mm	Unit	Net EUR/100 items at a purchase of		
							up to 100	101 - 500	501 - 1000
98173	M16 x 1,5	1/4"	11,5	22,0	12,0	25	o. r.	o. r.	o. r.
98174	M20 x 1,5	1/4"	11,5	22,0	12,0	25	o. r.	o. r.	o. r.
98171	M16 x 1,5	5/16"	14,4	22,0	12,0	25	o. r.	o. r.	o. r.
98172	M20 x 1,5	5/16"	14,4	22,0	12,0	25	o. r.	o. r.	o. r.
98175	M16 x 1,5	3/8"	17,8	29,0	16,0	25	o. r.	o. r.	o. r.
98176	M20 x 1,5	3/8"	17,8	29,0	16,0	25	o. r.	o. r.	o. r.
98177	M20 x 1,5	1/2"	21,1	35,0	16,0	25	o. r.	o. r.	o. r.
98178	M25 x 1,5	3/4"	26,4	42,0	16,0	25	o. r.	o. r.	o. r.
98179	M32 x 1,5	1"	33,1	47,0	15,0	5	o. r.	o. r.	o. r.

PG thread

Part no.	Size	Suitable for tube ND	Suitable for tube outer Ø mm	Spanner size mm	Thread length mm	Unit	Net EUR/100 items at a purchase of		
							up to 100	101 - 500	501 - 1000
90684	9	5/16"	14,4	26,0	12,0	25	o. r.	o. r.	o. r.
90685	11	3/8"	17,8	29,0	14,0	25	o. r.	o. r.	o. r.
90686	13,5	3/8"	17,8	29,0	14,0	25	o. r.	o. r.	o. r.
90687	16	1/2"	21,1	35,0	14,0	25	o. r.	o. r.	o. r.
90688	21	3/4"	26,4	42,0	14,0	25	o. r.	o. r.	o. r.
90689	29	1"	33,1	47,0	19,0	5	o. r.	o. r.	o. r.
90690	36	1 1/4"	41,8	58,0	21,0	5	o. r.	o. r.	o. r.
90691	42	1 1/2"	47,8	69,0	21,0	2	o. r.	o. r.	o. r.
90692	48	2"	59,9	83,0	21,0	1	o. r.	o. r.	o. r.

Continuation ►

o. r. = on request

T&B conduit gland - straight



NPT thread

Part no.	Size	Suitable for tube ND	Suitable for tube outer Ø mm	Spanner size mm	Thread length mm	Unit	Net EUR/100 Items at a purchase of		
							up to 100	101 - 500	501 - 1000
98190	1/4"	1/4"	11,5	21,0	12,0	25	o. r.	o. r.	o. r.
98191	3/8"	5/16"	14,4	25,0	12,0	25	o. r.	o. r.	o. r.
96737	1/2"	3/8"	17,8	29,0	14,0	25	o. r.	o. r.	o. r.
90810	1/2"	1/2"	21,1	35,0	14,0	25	o. r.	o. r.	o. r.
96465	3/4"	3/4"	26,4	42,0	14,0	25	o. r.	o. r.	o. r.
96205	1"	1"	33,1	48,0	19,0	10	o. r.	o. r.	o. r.
98192	1 1/4"	1 1/4"	41,8	58,0	21,0	5	o. r.	o. r.	o. r.
96206	1 1/2"	1 1/2"	47,8	69,0	21,0	2	o. r.	o. r.	o. r.
96207	2"	2"	59,9	83,0	22,0	1	o. r.	o. r.	o. r.
98193	2 1/2"	2 1/2"	72,6	95,0	25,0	1	o. r.	o. r.	o. r.
98194	3"	3"	88,4	114,0	25,0	1	o. r.	o. r.	o. r.
98195	4"	4"	-	140,0	29,0	1	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request