

T tubular cable lug - straight

not insulated - with inspection hole



Tubular cable lugs T


Non-insulated tubular cable lugs in eye type design.

Material

Copper
Surface: tinned

Technical data

Temperature range: up to +125°C



Dimensions

- a Diameter of the boring
- d Inner diameter of the cable insertion
- b Flange width
- l Length till middle of the boring

eye type

Part no.	Type	Cross-section mm ²	a mm	d mm	b mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
										up to 500	501 - 1000	1001 - 5000
91458	T 1,5-4	1,5	4,3	2,3	8,0	15,2	-	1,6	100	o. r.	o. r.	o. r.
91459	T 1,5-5	1,5	5,3	2,3	8,0	15,2	-	1,7	100	o. r.	o. r.	o. r.
91460	T 2,5-4	2,5	4,3	2,6	6,9	15,2	-	1,1	100	o. r.	o. r.	o. r.
91461	T 2,5-5	2,5	5,3	2,6	7,6	15,2	-	1,1	100	o. r.	o. r.	o. r.
91462	T 2,5-6	2,5	6,4	2,6	9,1	16,7	-	1,4	100	o. r.	o. r.	o. r.
91463	T 4-4	4,0	4,3	3,3	8,0	19,4	-	2,5	50	o. r.	o. r.	o. r.
91464	T 4-5	4,0	5,3	3,3	10,0	19,9	-	2,7	50	o. r.	o. r.	o. r.
91465	T 4-6	4,0	6,4	3,3	11,0	20,9	-	2,8	50	o. r.	o. r.	o. r.
91467	T 6-5	6,0	5,3	3,5	10,0	20,5	-	5,5	100	o. r.	o. r.	o. r.
91468	T 6-6	6,0	6,4	3,5	12,0	20,5	-	5,4	100	o. r.	o. r.	o. r.
91469	T 10-6	10,0	6,4	4,5	12,0	22,5	-	5,3	100	o. r.	o. r.	o. r.
91470	T 10-8	10,0	8,4	4,5	15,0	25,0	-	6,4	100	o. r.	o. r.	o. r.
91471	T 10-10	10,0	10,5	4,5	17,0	27,0	-	7,0	100	o. r.	o. r.	o. r.
91472	T 16-6	16,0	6,4	5,5	12,0	27,0	-	9,2	100	o. r.	o. r.	o. r.
91473	T 16-8	16,0	8,4	5,5	15,0	29,0	-	10,1	100	o. r.	o. r.	o. r.
91474	T 16-10	16,0	10,5	5,5	17,0	31,0	-	10,9	100	o. r.	o. r.	o. r.
91561	T 25-6	25,0	6,4	7,0	14,0	30,0	-	12,7	100	o. r.	o. r.	o. r.
91562	T 25-8	25,0	8,4	7,0	16,0	32,5	-	15,9	100	o. r.	o. r.	o. r.
91563	T 25-10	25,0	10,5	7,0	18,0	34,5	-	15,2	100	o. r.	o. r.	o. r.
91564	T 25-12	25,0	13,2	7,0	19,0	35,5	-	15,0	100	o. r.	o. r.	o. r.
91565	T 35-6	35,0	6,4	8,5	17,0	32,5	-	19,3	100	o. r.	o. r.	o. r.
91566	T 35-8	35,0	8,4	8,5	17,0	35,0	-	21,4	100	o. r.	o. r.	o. r.
91567	T 35-10	35,0	10,5	8,5	19,0	37,0	-	22,9	100	o. r.	o. r.	o. r.
91568	T 35-12	35,0	13,2	8,5	21,0	38,0	-	22,3	100	o. r.	o. r.	o. r.
91569	T 50-6	50,0	6,4	10,0	20,0	37,0	-	30,9	100	o. r.	o. r.	o. r.
91570	T 50-8	50,0	8,4	10,0	20,0	37,0	-	30,1	100	o. r.	o. r.	o. r.
91571	T 50-10	50,0	10,5	10,0	20,0	39,0	-	31,7	100	o. r.	o. r.	o. r.
91572	T 50-12	50,0	13,2	10,0	23,0	40,0	-	31,8	100	o. r.	o. r.	o. r.

Continuation ►

o. r. = on request

T tubular cable lug - straight

not insulated - with inspection hole

eye type

Part no.	Type	Cross-section mm ²	a mm	d mm	b mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
										up to 500	501 - 1000	1001 - 5000
91573	T 70-8	70,0	8,4	12,0	23,0	43,0	-	45,5	50	o. r.	o. r.	o. r.
91574	T 70-10	70,0	10,5	12,0	23,0	45,0	-	48,8	50	o. r.	o. r.	o. r.
91575	T 70-12	70,0	13,2	12,0	23,0	46,0	-	48,0	50	o. r.	o. r.	o. r.
91577	T 95-8	95,0	8,4	13,5	26,0	48,0	-	58,4	50	o. r.	o. r.	o. r.
91578	T 95-10	95,0	10,5	13,5	26,0	48,0	-	57,2	50	o. r.	o. r.	o. r.
91493	T 95-12	95,0	13,2	13,5	26,0	49,0	-	56,7	50	o. r.	o. r.	o. r.
96317	T 120-8	120,0	8,4	15,0	28,0	51,0	-	68,9	50	o. r.	o. r.	o. r.
91495	T 120-10	120,0	10,5	15,0	28,0	51,0	-	67,7	50	o. r.	o. r.	o. r.
91496	T 120-12	120,0	13,2	15,0	28,0	51,0	-	65,8	50	o. r.	o. r.	o. r.
91498	T 120-16	120,0	17,0	15,0	30,0	53,0	-	66,6	50	o. r.	o. r.	o. r.
97690	T 120-20	120,0	21,0	15,0	36,0	59,0	-	77,6	50	o. r.	o. r.	o. r.
97872	T 150-8	150,0	8,4	16,5	31,0	58,0	-	77,9	50	o. r.	o. r.	o. r.
91499	T 150-10	150,0	10,5	16,5	31,0	58,0	-	76,8	50	o. r.	o. r.	o. r.
91500	T 150-12	150,0	13,2	16,5	31,0	58,0	-	75,1	50	o. r.	o. r.	o. r.
91502	T 150-16	150,0	17,0	16,5	31,0	58,0	-	71,9	50	o. r.	o. r.	o. r.
96318	T 185-10	185,0	10,5	19,0	35,0	65,0	-	119,8	50	o. r.	o. r.	o. r.
91503	T 185-12	185,0	13,2	19,0	35,0	65,0	-	117,7	50	o. r.	o. r.	o. r.
91505	T 185-16	185,0	17,0	19,0	35,0	65,0	-	113,9	50	o. r.	o. r.	o. r.
91506	T 185-20	185,0	21,0	19,0	39,0	69,0	-	118,0	50	o. r.	o. r.	o. r.
93669	T 240-10	240,0	10,5	21,0	39,0	72,0	-	173,6	50	o. r.	o. r.	o. r.
96962	T 240-12	240,0	13,2	21,0	39,0	72,0	-	171,2	50	o. r.	o. r.	o. r.
91508	T 240-16	240,0	17,0	21,0	39,0	72,0	-	166,7	50	o. r.	o. r.	o. r.
91509	T 240-20	240,0	21,0	21,0	39,0	72,0	-	160,8	50	o. r.	o. r.	o. r.
96319	T 300-12	300,0	13,2	23,4	43,0	77,3	-	228,6	10	o. r.	o. r.	o. r.
91510	T 300-16	300,0	17,0	23,4	43,0	80,3	-	249,3	10	o. r.	o. r.	o. r.
91511	T 300-20	300,0	21,0	23,4	43,0	86,3	-	253,2	10	o. r.	o. r.	o. r.
91512	T 400-20	400,0	21,0	26,7	49,5	90,3	-	349,7	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request