

UNI-DICHT-VK-PA gland body



UNI-DICHT-VK-PA

Gland body made of polyamide for populating with sealing inserts made by TPE.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Polyamide PA6-3

Note

The gland body M20x1,5 part no. 903941 is used with inserts PG 11; also part no. 90831 is used with inserts PG 13,5.

Technical data

Temperature range: -20°C up to +100°C

Test standard: EN50262



Dimensions

G Thread size
GL Thread length
SW Spanner size

metric thread

Part no. grey RAL 7032	Size Metr.	Thread length mm	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
					up to 100	101 - 500	501 - 1000
90829	M12 x 1,5	8,0	15	50	o. r.	o. r.	o. r.
90830	M16 x 1,5	9,0	19	50	o. r.	o. r.	o. r.
903941	M20 x 1,5	9,0	24	50	o. r.	o. r.	o. r.
90831	M20 x 1,5	9,0	24	50	o. r.	o. r.	o. r.
90832	M25 x 1,5	9,0	29	50	o. r.	o. r.	o. r.
90833	M32 x 1,5	11,0	38	25	o. r.	o. r.	o. r.
90834	M40 x 1,5	11,5	46	10	o. r.	o. r.	o. r.
90835	M50 x 1,5	14,0	55	5	o. r.	o. r.	o. r.

PG thread

Part no. grey RAL 7032	Size PG	Thread length mm	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
					up to 100	101 - 500	501 - 1000
96043	9	9,0	19	50	o. r.	o. r.	o. r.
96044	11	9,0	22	50	o. r.	o. r.	o. r.
96045	13,5	9,0	24	50	o. r.	o. r.	o. r.
96046	16	9,0	27	50	o. r.	o. r.	o. r.
96047	21	11,0	33	25	o. r.	o. r.	o. r.
96048	29	11,0	43	10	o. r.	o. r.	o. r.
96049	36	14,0	53	5	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request