


W tubular cable lug - angulated 90° not insulated



Elbow tubular lugs W 90°
Non-insulated tubular lugs in eye type design, 90° angled.

Material
Copper
Surface: tinned

Technical data
Temperature range: up to +120°C



Dimensions
a Diameter of boring
d Inner diameter of the cable insertion
b Flange width

eye type

Part no. 90°	Type	Cross-section mm²	a mm	d mm	b mm	Weight kg / 1000 Stück	Unit	Net EUR/100 items at a purchase of		
								up to 100	101 - 500	501 - 1000
90866	W 6-5	6,0	5,3	3,5	10,0	6,0	100	o. r.	o. r.	o. r.
96303	W 6-6	6,0	6,4	3,5	12,0	5,9	100	o. r.	o. r.	o. r.
90867	W 6-8	6,0	8,4	3,5	15,0	6,7	100	o. r.	o. r.	o. r.
90868	W 6-10	6,0	10,5	3,5	17,0	7,2	100	o. r.	o. r.	o. r.
90869	W 6-12	6,0	13,2	3,5	19,0	7,7	100	o. r.	o. r.	o. r.
90939	W 10-5	10,0	5,3	4,5	12,0	6,0	100	o. r.	o. r.	o. r.
96309	W 10-6	10,0	6,4	4,5	12,0	5,9	100	o. r.	o. r.	o. r.
96908	W 10-8	10,0	8,4	4,5	15,0	6,7	100	o. r.	o. r.	o. r.
90940	W 10-10	10,0	10,5	4,5	17,0	7,2	100	o. r.	o. r.	o. r.
90941	W 10-12	10,0	13,2	4,5	19,0	7,6	100	o. r.	o. r.	o. r.
90942	W 16-5	16,0	5,3	5,5	12,0	10,1	100	o. r.	o. r.	o. r.
96308	W 16-6	16,0	6,4	5,5	12,0	10,0	100	o. r.	o. r.	o. r.
96907	W 16-8	16,0	8,4	5,5	15,0	11,0	100	o. r.	o. r.	o. r.
96310	W 16-10	16,0	10,5	5,5	17,0	11,7	100	o. r.	o. r.	o. r.
90943	W 16-12	16,0	13,2	5,5	19,0	12,3	100	o. r.	o. r.	o. r.
90944	W 25-5	25,0	5,3	7,0	14,0	13,4	100	o. r.	o. r.	o. r.
98377	W 25-6	25,0	6,4	7,0	14,0	13,1	100	o. r.	o. r.	o. r.
90945	W 25-8	25,0	8,4	7,0	16,0	14,7	100	o. r.	o. r.	o. r.
90946	W 25-10	25,0	10,5	7,0	18,0	15,6	100	o. r.	o. r.	o. r.
90947	W 25-12	25,0	13,2	7,0	19,0	16,0	100	o. r.	o. r.	o. r.
90949	W 35-6	35,0	6,4	8,5	17,0	20,4	100	o. r.	o. r.	o. r.
90950	W 35-8	35,0	8,4	8,5	17,0	22,8	100	o. r.	o. r.	o. r.
96313	W 35-10	35,0	10,5	8,5	19,0	23,9	100	o. r.	o. r.	o. r.
90951	W 35-12	35,0	13,2	8,5	21,0	25,4	100	o. r.	o. r.	o. r.
90953	W 35-16	35,0	17,0	8,5	26,0	0,0	25	o. r.	o. r.	o. r.
90954	W 50-6	50,0	6,4	10,0	20,0	31,6	100	o. r.	o. r.	o. r.
96314	W 50-8	50,0	8,4	10,0	20,0	33,8	100	o. r.	o. r.	o. r.
90955	W 50-10	50,0	10,5	10,0	20,0	35,2	100	o. r.	o. r.	o. r.
90956	W 50-12	50,0	13,2	10,0	23,0	38,0	100	o. r.	o. r.	o. r.
90958	W 50-16	50,0	17,0	10,0	28,0	0,0	25	o. r.	o. r.	o. r.
90959	W 50-20	50,0	21,0	10,0	30,0	0,0	25	o. r.	o. r.	o. r.

Continuation ►

o. r. = on request

W tubular cable lug - angulated 90°

not insulated

eye type

Part no. 90°	Type	Cross-section mm²	a mm	d mm	b mm	Weight kg / 1000 Stück	Unit	Net EUR/100 items at a purchase of		
								up to 100	101 - 500	501 - 1000
90960	W 70-6	70,0	6,5	12,0	23,0	0,0	25	o. r.	o. r.	o. r.
90961	W 70-8	70,0	8,4	12,0	23,0	50,9	100	o. r.	o. r.	o. r.
96315	W 70-10	70,0	10,5	12,0	23,0	53,4	100	o. r.	o. r.	o. r.
96316	W 70-12	70,0	13,2	12,0	23,0	54,4	100	o. r.	o. r.	o. r.
90963	W 70-16	70,0	17,0	12,0	26,0	58,5	100	o. r.	o. r.	o. r.
90964	W 70-20	70,0	21,0	12,0	30,0	0,0	25	o. r.	o. r.	o. r.
90965	W 95-8	95,0	8,4	13,5	26,0	61,1	50	o. r.	o. r.	o. r.
97672	W 95-10	95,0	10,5	13,5	26,0	62,7	50	o. r.	o. r.	o. r.
90966	W 95-12	95,0	13,2	13,5	26,0	64,8	50	o. r.	o. r.	o. r.
90968	W 95-16	95,0	17,0	13,5	28,0	71,2	50	o. r.	o. r.	o. r.
90969	W 95-20	95,0	21,0	13,5	30,0	0,0	25	o. r.	o. r.	o. r.
90970	W 120-8	120,0	8,4	15,0	28,0	66,9	50	o. r.	o. r.	o. r.
90971	W 120-10	120,0	10,5	15,0	28,0	71,0	50	o. r.	o. r.	o. r.
90972	W 120-12	120,0	13,2	15,0	28,0	72,3	50	o. r.	o. r.	o. r.
90974	W 120-16	120,0	17,0	15,0	30,0	78,1	50	o. r.	o. r.	o. r.
90975	W 120-20	120,0	21,0	15,0	36,0	0,0	10	o. r.	o. r.	o. r.
90976	W 150-8	150,0	8,5	16,5	31,0	0,0	10	o. r.	o. r.	o. r.
90977	W 150-10	150,0	10,5	16,5	31,0	0,0	10	o. r.	o. r.	o. r.
90978	W 150-12	150,0	13,0	16,5	31,0	0,0	10	o. r.	o. r.	o. r.
90980	W 150-16	150,0	17,0	16,5	31,0	0,0	10	o. r.	o. r.	o. r.
90981	W 150-20	150,0	21,0	16,5	36,0	0,0	10	o. r.	o. r.	o. r.
90982	W 185-10	185,0	10,5	19,0	35,0	0,0	10	o. r.	o. r.	o. r.
90983	W 185-12	185,0	13,0	19,0	35,0	0,0	10	o. r.	o. r.	o. r.
90985	W 185-16	185,0	17,0	19,0	35,0	0,0	10	o. r.	o. r.	o. r.
90986	W 185-20	185,0	21,0	19,0	39,0	0,0	10	o. r.	o. r.	o. r.
90987	W 240-10	240,0	10,5	21,0	39,0	0,0	10	o. r.	o. r.	o. r.
90988	W 240-12	240,0	13,0	21,0	39,0	0,0	10	o. r.	o. r.	o. r.
90990	W 240-16	240,0	17,0	21,0	39,0	0,0	10	o. r.	o. r.	o. r.
90991	W 240-20	240,0	21,0	21,0	39,0	0,0	10	o. r.	o. r.	o. r.
90992	W 300-12	300,0	13,0	23,5	43,0	0,0	5	o. r.	o. r.	o. r.
90994	W 300-16	300,0	17,0	23,5	43,0	0,0	5	o. r.	o. r.	o. r.
90995	W 300-20	300,0	21,0	23,5	43,0	0,0	5	o. r.	o. r.	o. r.
90996	W 400-12	400,0	13,0	27,0	49,0	0,0	5	o. r.	o. r.	o. r.
90998	W 400-16	400,0	17,0	27,0	49,0	0,0	5	o. r.	o. r.	o. r.
90999	W 400-20	400,0	21,0	27,0	49,0	0,0	5	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request