



WVF

Profile for simple cable insertion.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material


Die-cast zinc
O-ring: chloroprene-rubber (CR)

Technical data

Protection class: IP 68 - 10 bar

Temperature range: -20°C up to +100°C

Test standard: EN50262



Abmessungen

G Thread size inside
H Height
B Width
L Length

metric female thread

Part no.	Size Metr. innen	Height mm	Width mm	Length mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
91730	M20 x 1,5	35,0	53,0	56,0	10	o. r.	o. r.	o. r.
91731	M25 x 1,5	42,0	63,0	65,0	10	o. r.	o. r.	o. r.
91732	M32 x 1,5	52,0	70,0	75,0	5	o. r.	o. r.	o. r.
91733	M40 x 1,5	52,0	71,0	75,0	5	o. r.	o. r.	o. r.
91734	M50 x 1,5	69,0	89,0	93,0	2	o. r.	o. r.	o. r.
91735	M63 x 1,5	74,0	96,0	114,0	1	o. r.	o. r.	o. r.

PG thread

Part no.	Size PG innen	Height mm	Width mm	Length mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
92930	9	30,0	45,0	48,0	10	o. r.	o. r.	o. r.
92931	11	30,0	45,0	48,0	10	o. r.	o. r.	o. r.
92932	13,5	35,0	53,0	56,0	10	o. r.	o. r.	o. r.
92933	16	35,0	53,0	56,0	10	o. r.	o. r.	o. r.
92934	21	42,0	63,0	65,0	5	o. r.	o. r.	o. r.
92935	29	52,0	71,0	75,0	5	o. r.	o. r.	o. r.
92936	36	69,0	89,0	94,0	2	o. r.	o. r.	o. r.
92937	42	74,0	96,0	114,0	1	o. r.	o. r.	o. r.
92938	48	74,0	96,0	114,0	1	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request