




ZE
For relieving strain on lines.

Material
Brass, nickel plated

Technical data
Temperature range: up to +200°C

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction



Dimensions

G Thread size
GL Thread length
SW Spanner size
H Height without thread

metric thread

Part no.	Size Metr.	Thread length mm	Spanner size mm	Height mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
905877	M12 x 1,5	5,5	16	9,5	100	o. r.	o. r.	o. r.
905878	M16 x 1,5	6,0	19	10,0	100	o. r.	o. r.	o. r.
905879	M20 x 1,5	6,5	24	11,5	50	o. r.	o. r.	o. r.
905880	M25 x 1,5	8,0	34	13,0	50	o. r.	o. r.	o. r.
905881	M32 x 1,5	8,0	42	14,0	25	o. r.	o. r.	o. r.
905882	M40 x 1,5	9,5	52	16,0	25	o. r.	o. r.	o. r.
905883	M50 x 1,5	9,5	52	16,0	10	o. r.	o. r.	o. r.

PG thread

Part no.	Size PG	Thread length mm	Spanner size mm	Height mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
99049	7	5,5	16	9,3	100	o. r.	o. r.	o. r.
99050	9	6,0	19	10,6	100	o. r.	o. r.	o. r.
99051	11	6,0	22	10,7	100	o. r.	o. r.	o. r.
99052	13,5	6,5	24	11,3	50	o. r.	o. r.	o. r.
99053	16	6,5	26	11,8	50	o. r.	o. r.	o. r.
99054	21	7,5	33	13,3	50	o. r.	o. r.	o. r.
99055	29	8,0	42	13,8	25	o. r.	o. r.	o. r.
99056	36	9,5	52	15,8	10	o. r.	o. r.	o. r.
99057	42	10,0	59	16,3	10	o. r.	o. r.	o. r.
99058	48	11,0	64	16,3	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request